

TECHNICAL DATA SHEET

Polyvinyl Chloride Resin

TECHNICAL DATA SHEET

Polyvinyl Chloride Resin

Product Polyvinyl Chloride Resin

Chemical Formula $(C_2H_3Cl)_n$

Cas No 9002-86-2

Print Date May 10th, 2020

Description

Features thermo plasticity, being insoluble into water, gasoline and alcohol, swelled or dissolved into ether, ketone, chlorinated aliphatic hydrocarbons, and aromatic hydrocarbon, high resistance to corrosion, and good dielectric property.

Applications

Widely used in pvc pipes, window profiles, films, sheets, tubes, shoes, fittings, etc.

Packaging

In 25kg kraft bag or 1100kg jumbo bag.

ITEMS	HS-1300	HS-1000R	HS-800	HS-700	
Viscosity(ml/g)	127-135	107-118	87-95	73-86	
K value	71-72	66-68	60-62	55-59	
Impurity particle number \leq	16	16	16	16	
Volatiles(incl.water) % \leq	0.30	0.30	0.30	0.30	
Bulk density g/ml \geq	0.48	0.53	0.53	0.53	
Sieve ratio%	0.25mm \leq	1.0	1.0	2.0	2.0
	0.063mm \geq	98	98	97	97
"Fish eye" number unit /400cm ² \leq	10	10	20	20	
100g resin plasticizer absorbtion g \geq	28	19	16	14	
Whiteness(after 160°C 10min) \geq	80	80	80	80	
Residual VCM ppm \leq	1.0	1.0	1.0	1.0	